

## CLAMP-ONE

Pinza amperometrica digitale wireless

- Valore massimo di 3999.
- Puntali di alta qualità.
- Misurazione Corrente AC fino a 1000A.
- Circuito ohmico, diodo, continuità, capacità, frequenza protettivo fino a 750V AC/DC rms.
- Test diodo con cicalino di verifica della continuità.
- Auto-spegnimento per preservare la durata della batteria.
- Display retroilluminato.
- Provvisto di DATA-HOLD, RELATIVE.
- Dotata di sonda di temperatura esterna.



INDISPENSABILE  
PER CONTROLLARE  
L'APPARECCHIATURA INVERTER



## Specifiche elettriche

|             | Range                                           |
|-------------|-------------------------------------------------|
| Tensione DC | 400mV, 4V, 40V, 400V, 1000V                     |
| Tensione AC | 4V, 40V, 400V, 750V                             |
| Corrente DC | 200A, 1000A                                     |
| Corrente AC | 400A, 1000A                                     |
| Resistenza  | 400Ω, 40KΩ, 400KΩ, 4MΩ, 40MΩ                    |
| Capacità    | 5124F, 5, 124F, 51.24F, 100 4F                  |
| Temperatura | -20 ÷ 1000 °C                                   |
| Frequenza   | 5.12Hz, 51.2Hz, 512Hz, 5.12kHz, 512kHz, 5.12MHz |
| Ciclo Duty  | 0.1% ÷ 99.9%                                    |



## Taratura

| Codice      | Modello      | Descrizione                               |
|-------------|--------------|-------------------------------------------|
| 09053017    |              | Rapporto taratura rif. Accredia per pinza |
| 09006008001 | CLAMP-ONE/CT | Pinza completa di rapporto taratura       |

INTERCONNESSIONE  
CON FOX-ONE



PHONE  
APP



## CLAMP-ONE

Wireless digital clamp-on meter

- Maximum reading of 3999.
- Heavy duty test leads.
- ACA Measurement up to 1000A.
- Ohm, Diode, Continuity, Capacitance, Frequency and Duty input Protection to 750V DA/AC rms.
- Diode test and Audible continuity check function.
- Auto power off to preserve battery life.
- Display back-light feature.
- Provides DATA-HOLD, RELATIVE.
- Complete of external temperature probe.

| Code     | Model     | Dimensions       | Weight  |
|----------|-----------|------------------|---------|
| 09006008 | CLAMP-ONE | 225 x 97 x 40 mm | 0,45 kg |



## Electrical specifications

|              | Range                                           |
|--------------|-------------------------------------------------|
| DC voltage   | 400mV, 4V, 40V, 400V, 1000V                     |
| AC voltage   | 4V, 40V, 400V, 750V                             |
| DC current   | 200A, 1000A                                     |
| AC current   | 400A, 1000A                                     |
| Resistance   | 400Ω, 40KΩ, 400KΩ, 4MΩ, 40mΩ                    |
| Quantity     | 5124F, 5, 124F, 51.24F, 100 4F                  |
| Temperature  | -20 to 1000 °C                                  |
| Frequency    | 5.12Hz, 51.2Hz, 512Hz, 5.12kHz, 512kHz, 5.12MHz |
| Duty current | 0.1% to 99.9%                                   |



## Calibration

| Code        | Model        | Description                                         |
|-------------|--------------|-----------------------------------------------------|
| 09053017    |              | Calibration report ref. Accredia for clamp-on meter |
| 09006008001 | CLAMP-ONE/CT | Clamp-on meter with calibration report              |

INDISPENSABLE FOR INVERTER  
UNITS CHECK



COMPATIBLE APPS  
WITH FOX-ONE



PHONE  
APP

