

## RELAYS



### ICG

Relays per sistemi frigoriferi senza condensatori di spunto.

| Codice   | Modello | Dimensioni        | Peso    |
|----------|---------|-------------------|---------|
| 09016002 | ICG-220 | 140 x 120 x 20 mm | 0,05 kg |



### RO

Relays con combinazione di sovraccarico.

| Codice   | Modello | Dimensioni        | Peso    |
|----------|---------|-------------------|---------|
| 09016001 | RO-82   | 140 x 120 x 40 mm | 0,07 kg |
| 09016004 | RO-62   | 140 x 120 x 40 mm | 0,07 kg |
| 09016003 | RO-42   | 140 x 120 x 40 mm | 0,07 kg |



### PO

Relays per sistemi frigoriferi senza condensatori di spunto.

| Codice   | Modello | Dimensioni        | Peso    |
|----------|---------|-------------------|---------|
| 09016017 | PO-230  | 120 x 100 x 20 mm | 0,03 kg |



### RCO

Relays di avviamento 3 in 1.

| Codice   | Modello | Dimensioni        | Peso    |
|----------|---------|-------------------|---------|
| 09016033 | RCO-820 | 190 x 180 x 40 mm | 0,20 kg |
| 09016009 | RCO-620 | 190 x 180 x 40 mm | 0,20 kg |
| 09016011 | RCO-420 | 190 x 180 x 40 mm | 0,20 kg |



### Tabella comparativa

|                         | ICG-220       | PO-230        | RO-82         | RO-62         | RO-42         | RCO-820       | RCO-620       | RCO-420       |
|-------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Relay                   | X             | X             | X             | X             | X             | X             | X             | X             |
| Sovraccarico            | -             | -             | X             | X             | X             | X             | X             | X             |
| Condensatore avviamento | -             | -             | -             | -             | -             | X             | X             | X             |
| Montaggio               | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect |
| Potenza HP              | 1/12÷1/2      | 1/12÷1/2      | 1/12÷1/8      | 1/6÷1/5       | 1/4÷1/3       | 1/12÷1/8      | 1/6÷1/5       | 1/4÷1/3       |
| Vtaggio                 | 230           | 230           | 230           | 230           | 230           | 230           | 230           | 230           |

## RELAYS



### ICG

Relays and hard starts for refrigeration systems without run capacitors.

| Code     | Model   | Dimensions        | Weight  |
|----------|---------|-------------------|---------|
| 09016002 | ICG-220 | 140 x 120 x 20 mm | 0,05 kg |



### RO

Relays and hard starts for refrigeration systems without run capacitors.

| Code     | Model | Dimensions        | Weight  |
|----------|-------|-------------------|---------|
| 09016001 | RO-82 | 140 x 120 x 40 mm | 0,07 kg |
| 09016004 | RO-62 | 140 x 120 x 40 mm | 0,07 kg |
| 09016003 | RO-42 | 140 x 120 x 40 mm | 0,07 kg |



### PO

Relays with overload combination.

| Code     | Model  | Dimensions        | Weight  |
|----------|--------|-------------------|---------|
| 09016017 | PO-230 | 120 x 100 x 20 mm | 0,03 kg |



### RCO

3 n° 1 Start Relay.

| Code     | Model   | Dimensions        | Weight  |
|----------|---------|-------------------|---------|
| 09016033 | RCO-820 | 190 x 180 x 40 mm | 0,20 kg |
| 09016009 | RCO-620 | 190 x 180 x 40 mm | 0,20 kg |
| 09016011 | RCO-420 | 190 x 180 x 40 mm | 0,20 kg |



### Comparative table

|                 | ICG-220       | PO-230        | RO-82         | RO-62         | RO-42         | RCO-820       | RCO-620       | RCO-420       |
|-----------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Relay           | x             | x             | x             | x             | x             | x             | x             | x             |
| Overload        | -             | -             | x             | x             | x             | x             | x             | x             |
| Start capacitor | -             | -             | -             | -             | -             | x             | x             | x             |
| Mounting        | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect | Quick connect |
| HP rating       | 1/12 to 1/2   | 1/12 to 1/2   | 1/1 2to 1/8   | 1/6 to 1/5    | 1/4 to 1/3    | 1/12 to 1/8   | 1/6 to 1/5    | 1/4 to 1/3    |
| Voltage         | 230           | 230           | 230           | 230           | 230           | 230           | 230           | 230           |