

KIT UUOTO E CARICA CADDY FOX 5/100



INCLUSO
R32

INCLUSO
R1234ZE

CADDY FOX 5/100

Kit universale per uuoto e carica con gruppo manometrico digitale e bilancia (5 o 100 kg)

Possibilità di lavorare con oltre 50 refrigeranti.

Dimensioni ridotte e estrema facilità di trasporto.

Dotazione standard:

- Pompa per uuoto doppio stadio con elettrovalvola e vacuometro 46 lt/min o 110 lt/min.
- Gruppo manometrico digitale FOX-300 in valigetta con 2 sonde TK109, 2 tubi flessibili 1500 mm con valvola intermedia - blu e rosso, 1 tubo flessibile 1500 mm con valvola finale - giallo, 1 tubo flessibile per uuoto IPERVAC 900 mm - 3/8" SAE e 2 raccordi girevoli RG180/5-4 - 5/16" F x 1/4" SAE M.
- Flacone olio minerale.

Versione CADDY FOX 5

- Bilancia elettronica da 5 kg, con risoluzione 1 g.
- 3 supporti per bombole (1/4" x 1/4" - 5/16" x 1/4" - 1/2"-16 ACME Sx x 1/4" SAE).

Versione CADDY FOX 100

- Bilancia elettronica da 100 kg, con risoluzione 5 g.

KIT BASE CADDY FOX



BILANCIA PER CADDY FOX 100



BILANCIA PER CADDY FOX 5



Caratteristiche tecniche

	CADDY 46D/5/FOX300	CADDY 110D/5/FOX300	CADDY 46D/100/FOX300	CADDY 110D/100/FOX300
Portata bilancia	5 kg	5 kg	100 kg	100 kg
Portata pompa	46 lt/min	110 lt/min	46 lt/min	110 lt/min
Vuoto finale	1x10 ⁻² mbar	1x10 ⁻² mbar	1x10 ⁻² mbar	1x10 ⁻² mbar

WELDING

**SPITFIRE/PRO**

Complete kit with 1 torch SPITFIRE and 2 MAP-HP cartridges

Features:

Large and high intensity flame.

Up to 2200°C high temperature powerful swirl flame.

For use with MAP-HP and Propane gas.

Piezo igniter for instant flame.

Safety lock feature to prevent accidental ignition.

Ignition button lock for continuous use.

Replaceable brass tip.

Ergonomic handle design.

Code	Model	Dimensions	Weight
10001037	SPITFIRE/PRO	310 x 270 x 120 mm	2,8 kg

**SPITFIRE**

Torch welders

Features:

Large and high intensity flame.

Up to 2200°C high temperature powerful swirl flame.

For use with MAP-HP and Propane gas.

Piezo igniter for instant flame.

Safety lock feature to prevent accidental ignition.

Ignition button lock for continuous use.

Replaceable brass tip.

Ergonomic handle design.

Code	Model	Dimensions	Weight
10001036	SPITFIRE	320 x 160 x 40 mm	0,46 kg



A



B

MAP-HP

New-generation cartridges MAP-HP

Ref	Code	Model	Description	Capacit	Min. Qty
A	11003022	MAP-HP	Cartridge	400 g	12
B	05055071	-	Adapter for use with TURBO SET 90	-	-

Ref	Code	Temperature	Dimensions	Weight
A	11003022	1982°C	470 x 160 x 280 mm	11,1kg
B	05055071		140 x 100 x 20 mm	0,10 kg